

Adhesive Remover QX264

Description and Applications

Adhesive Remover QX264 is specifically designed for removing fully cured polyurethane conformal coatings and certain partially cured UV conformal coatings.

Features

- Non-flammable.
- Highly effective remover specially formulated for cross-linked, cured polyurethane conformal coatings.
- Leaves no residue after evaporation.
- Non-corrosive to metal solder joints and fiberglass board coatings.

Product Properties

Item	Test Method	Specification
Appearance / Color	Visual Inspection	Clear Liquid
Solid Content	GB/T 1725-2007	None
Viscosity	GB/T 22235-2008	20 ± 10 mPa·s (25°C)
Specific Gravity	GB/T 6750-2007	1.2 ± 0.05

Note: For optimal removal performance, the product temperature should be maintained above 20°C. Ensure adequate ventilation during use.

Packaging

- 100 g / Bottle
- 1,000 g / Bottle
- 5,000 g / Pail

Instructions for Use

Before using this product, operators must wear:

- Full-body long-sleeved protective clothing

- Protective gloves (PE or nitrile solvent-resistant gloves)
- Safety goggles

Avoid direct skin contact with the remover.

This product has strong dissolving properties and may affect certain plastics, acrylic materials, and inks. Compatibility testing is strongly recommended before formal application.

Apply the remover evenly onto the coated surface using a brush. Within a few minutes, the coating will soften, wrinkle, and blister. Remove the loosened coating using an appropriate conformal coating thinner or a clean brush.

For thick or difficult-to-remove coatings, repeat the process until the coating is completely removed.

After removal, thoroughly clean and dry the substrate to eliminate any residue before proceeding with subsequent processes.

Precautions

- Ensure good ventilation during use to prevent the accumulation of high solvent vapor concentrations.
- Do not point the container opening toward your face when opening, as internal pressure may cause splashing.
- This product has strong degreasing properties. Avoid contact with skin and eyes, as it may cause irritation, allergic reactions, or a burning sensation.
- In case of skin contact, rinse immediately with plenty of clean water.

Storage

Store in a cool, dry, and well-ventilated area, away from direct sunlight, heat sources, and open flames.

Recommended storage temperature: 5°C to 25°C.

After opening, reseal the container tightly to maintain product quality and stability.